

AMENDMENTS TO THE CLAIMS

1-7. (Canceled)

8. (Previously Presented) A ground terminal comprising:

a ground terminal body formed into an annular shape as viewed in plan; and

at least one connection portion formed integrally with the ground terminal body, said connection portion being bendable and extending from an inner circumference of the ground terminal body toward a center of the ground terminal,

said ground terminal comprises a plurality of connection portions that are formed integrally with the ground terminal body and spaced from one another in a direction of the inner circumference of the ground terminal body, these connection portions being bendable and extending from the inner circumference of the ground terminal body toward the center of the ground terminal,

wherein each of the plurality of connection portions has a first and a second widthwise half, and the first widthwise half of each connection portion is formed at its tip end with a notch to which a tip end of the second widthwise half of an adjacent connection portion enters.

9. (Previously Presented) A ground terminal comprising:

a ground terminal body formed into an annular shape as viewed in plan; and

at least one connection portion formed integrally with the ground terminal body, said connection portion being bendable and extending from an inner circumference of the ground terminal body toward a center of the ground terminal,

wherein said ground terminal comprises a plurality of connection portions that are formed integrally with the ground terminal body and spaced from one another in a direction of the inner circumference of the ground terminal body, these connection portions being bendable and extending from the inner circumference of the ground terminal body toward the center of the ground terminal,

wherein among the plurality of connection portions, those connection portions other than a pair of opposed connection portions have their length shorter than a length of the paired connection portions, so that tip ends of the long connection portions enter between the short connection portions.

10. (Canceled)

11. (Currently Amended) The ground terminal according to claim [[4]] 9, wherein each of the plurality of connection portions of the ground terminal has a tip end thereof formed into an arcuate shape.

12. (Currently Amended) The ground terminal according to claim [[4]] 9, wherein the plurality of connection portions are comprised of two connection portions each having a wide tip end portion facing that of another connection portion.

13. (Previously Presented) A ground terminal comprising:
a ground terminal body formed into an annular shape as viewed in plan; and

at least one connection portion formed integrally with the ground terminal body, said connection portion being bendable and extending from an inner circumference of the ground terminal body toward a center of the ground terminal,

wherein said ground terminal comprises a plurality of connection portions that are formed integrally with the ground terminal body and spaced from one another in a direction of the inner circumference of the ground terminal body, these connection portions being bendable and extending from the inner circumference of the ground terminal body toward the center of the ground terminal,

wherein each of the plurality of connection portions is formed at its proximal portion with a hole.

14. (Currently Amended) The ground terminal according to claim ~~[[4]]~~ 13, wherein each of the plurality of connection portions is formed into an arrowhead shape whose proximal portion is narrow in width.

15. (Previously Presented) A ground terminal comprising:
a ground terminal body formed into an annular shape as viewed in plan; and
at least one connection portion formed integrally with the ground terminal body, said connection portion being bendable and extending from an inner circumference of the ground terminal body toward a center of the ground terminal,

said ground terminal comprises a plurality of connection portions that are formed integrally with the ground terminal body and spaced from one another in a direction of the inner

circumference of the ground terminal body, these connection portions being bendable and extending from the inner circumference of the ground terminal body toward the center of the ground terminal, each of the plurality of connection portions is formed into an arrowhead shape whose proximal portion is narrow in width,

wherein each of the plurality of connection portions is formed with an elongated hole extending along a longitudinal axis of the connection portion.

16. (Original) A method for mounting a printed board mounted with a ground terminal to a chassis, comprising the steps of:

(a) preparing a ground terminal comprising a ground terminal body formed into an annular shape as viewed in plan, and at least one connection portion formed integrally with the ground terminal body, the connection portion being bendable and extending from an inner circumference of the ground terminal body toward a center of the ground terminal;

(b) mounting the ground terminal on the printed board with the ground terminal body aligned with a mounting hole of the printed board; and

(c) placing the printed board mounted with the ground terminal on the chassis, with the mounting hole of the printed board aligned with a tapped hole of the chassis, and tightening a mounting screw inserted to the ground terminal body and the mounting hole of the printed board and threadedly engaged with the tapped hole of the chassis, thereby mounting the printed board to the chassis and causing the connection portion of the ground terminal to be bent in the mounting hole of the printed board and to be brought in direct contact with the chassis.

17. (Canceled)